GDI BELLMINI

Portable Gas Detector

An IGD exclusive, the GDI BELLMINI is a portable single gas detector that offers advanced personal protection in a lightweight ergonomic package. With sensor options for up to 18 different gases and user-friendly one-button operation, the BELLMINI guarantees the accurate, immediate detection of the target gas. The robust weather and dustproof build prevent ingress and the ultra-low power design ensures a two-year battery life. Stay alert to threats with clear audible, visual and vibrating alarms, manage real-time data via the IoT and collect advanced data logs via the BELLCONNECT™ App.



High-performance sensor technology and advanced signal processing ensure accurate monitoring of 18 different gases.

Clear Alerts

View real-time readings on the LCD screen. LEDs provide clear visual alerts, along with loud audible and vibrating alarms to alert you to issues immediately.

Advanced-Data Management

Register up to 200 event logs, access real-time data, manage configuration and link to a smartphone via the BELLCONNECT™ App.

Compact and Robust Build

Ergonomic lightweight design in a compact package with IP68 waterproof and dustproof protection for use in extreme environments.

Easy to Use

Both sensors & batteries are easily replaceable. Our one-button system makes for easy operation.







Pocket-sized design paired with a robust build

Wireless communication over 10m

Taking design cues from early gas masks, and incorporating them into a compact, ergonomic design, GDI provides the very best in personal defence against gas hazards with the new BELLMINI. Exclusively stocked in Europe by IGD, the BELLMINI. single gas portable detector represents the cutting edge in portable gas hazard mitigation.



BELLCONNECT™ NFC & Bluetooth

For the user's or administrator's convenience, the BELLCONNECT™ allows them to change its configuration, perform calibration, or handily manage stored data.

Event & Data Logging

Stores up to 200 event logs
Stores up to 5,000 datalog data
Time period can be changed in the app



Seamlessly calibrate and bump test your BELL MINI through the app. The app provides live gas readings during calibration, allows you to set policy reminders and provides calibration certificates

Confidence Beep

The BELL MINI requires no charging but you need to know its still powered.

Easily setup a confidence beep to periodically alert you that your BELL MINI is still on and still protecting you.

SAFE Mode

When enabled, Safe Mode provides visual confirmation that no(monitored) hazardous gas is present.







Name & Location Of Monitor

Through the app you can assign the monitor to personnel or specific areas. These names appear on event and data log and calibration reports. Providing you with more accountability onsite.

Configuration (Full Monitor Setup)

Allows you to fully customise the BELL MINI to your application needs, easily on the app. From changing alarm levels, setting policies, changing data log intervals etc. Customisation through the app makes it your own BELL MINI.



Specifications

Model

BELLMINI™

Weight

105g (w/Belt Clip)

Humidity

5% to 95% RH (non-condensing)

Display

FSTN LCD Display (1.6 inc)

Alarm

Visual Alarm (LEDs), Vibrating Alarm, Audible Alarm (Buzzer; 100dB@10cm): Low, High, TWA, STEL

IP Rating

IP68

User Options

Adjustable alarm setpoints. Alarm Latching On/Off Adjustment of calibration and bump test interval Zero and gas calibration, Data download, FW update

Self-Test

Breakdown of sensor and circuirty, Battery

Battery

Lithium Battery size 2/3 AA 3.6V: 24months

Wireless Connection

Bluetooh Low Energy (BLE), Near Field Communication (NFC), BELLCONNECT™ App, Cloud Connection, Easy close-range connection

Approvals

ATEX: Ex II 1G Ex ia IIC T4 Ga,

IEXEx: Ex ia IIC T4 Ga, KCs: Ex ia IIC T4

Data Logging

Up tp 200 alarm events, 5,000 data log

Warranty

2 years (Please referer to the Sensor data)

Gas List

- O2 - ETO

- CO - O3

- H2S - NO

- H2 - NO2

- SO2 - NH3

- Cl2 - CO-H

- HCI - CO-E

- HCN - O2-LF

- PH3 - NH3-H



BELLMINI Part Numbers

POR-GDIS-CO

POR-GDIS-H2S

POR-GDIS-COEX

POR-GDIS-CO-H

POR-GDIS-02

POR-GDIS-O2LF

POR-GDIS-H2

POR-GDIS-NH3

Name

BELL MINI CO SINGLE GAS PORTABLE

BELL MINI H2S SINGLE GAS PORTABLE

BELL MINI CO EX SINGLE GAS PORTABLE

BELL MINI CO H2 COMPENSATED SINGLE

GAS PORTABLE

BELL MINI O2 SINGLE GAS PORTABLE

BELL MINI O2LF SINGLE GAS PORTABLE

BELL MINI H2 SINGLE GAS PORTABLE

BELL MINI NH3 SINGLE GAS PORTABLE

Range

1-1000PPM

0.1-100PPM

1-2000PPM

1-500PPM

0.1-30%VOL

0.1-30%VOL

1-1000PPM

1-100PPM

Contact Us





internationalgasdetectors.com

Triton House, Crosby Street, Stockport SK2 6SH

